



CONTATORE  
ENERGIA



AVANQUADRO

LINEA PRINCIPALE  
CADUTA DI TENSIONE 1%



QUADRO  
GENERALE

LINEA DERIVATA  
CADUTA DI TENSIONE 3%



CARICO

MONOFASE (F-N) 230V

SEZIONE		(mm <sup>2</sup> )	1,5	2,5	4	6	10	16	25	35	50	70	95	120	150
PVC o gomma G, G1		I <sub>k</sub> (A)	19,5	27	36	46	63	85	110	137	167	213	258	299	344
Gomma G5, G7		I <sub>k</sub> (A)	24	33	45	58	80	107	135	169	207	268	328	382	441
I <sub>n</sub> Presi (A)	I <sub>n</sub> Interruttore (A)	I <sub>n</sub> Fusibile (A)	Lunghezza massima (m)												
		2	109	181	-	-	-	-	-	-	-	-	-	-	-
		4	55	91	-	-	-	-	-	-	-	-	-	-	-
	6		36	60	96	146	-	-	-	-	-	-	-	-	-
		6	36	60	-	-	-	-	-	-	-	-	-	-	-
		8	27	45	-	-	-	-	-	-	-	-	-	-	-
		10	22	36	58	87	145	230	365	504	683	-	-	-	-
		10	22	36	-	-	-	-	-	-	-	-	-	-	-
		12	18	30	-	-	-	-	-	-	-	-	-	-	-
		16	14	23	36	55	91	144	228	315	427	-	-	-	-
	16		14	23	-	-	-	-	-	-	-	-	-	-	-
		20	11	18	29	44	73	115	182	252	341	493	682	-	-
		20	/	18	29	44	-	-	-	-	-	-	-	-	-
		25	/	15	23	35	58	92	146	202	273	395	545	689	-
		25	/	15	23	35	-	-	-	-	-	-	-	-	-
		32	/	11	18	27	45	72	114	157	213	308	426	539	657
	32		/	/	18	27	-	-	-	-	-	-	-	-	-
		32	/	/	18	27	45	-	-	-	-	-	-	-	-
		40	/	/	14	22	36	57	91	126	171	247	341	431	525
		40	/	/	14	22	36	-	-	-	-	-	-	-	-
		50	/	/	/	17	29	46	73	101	137	197	273	345	420
		50	/	/	/	17	29	-	-	-	-	-	-	-	-
		63	/	/	/	/	23	37	58	80	108	157	216	274	334
	63		/	/	/	/	23	-	-	-	-	-	-	-	-